

# xpit

5 YEARS  
WARRANTY



## EN

Family of recessed adjustable spot lights, dustproof and waterproof (IP54), equipped with one COB LED.

Die-cast aluminum recessed frame, electrostatically painted with sandblasted finish. Electrostatically (liquid) painted for plastic parts, polycarbonate decorative ring.

Mounting element for the LED module in black polycarbonate with tilt angle indicator. The radiator of the LED modul from die-cast aluminum, electrostatically painted in black.

High-gloss faceted polycarbonate reflector.

Clear PMMA diffuser.

Silicone foam gasket.

Constant current LED driver delivered with the light fitting, connected by a sealed stainless steel gland.

Set of WAGO 2P clamps (0.08-2.5 mm<sup>2</sup>) for connecting the power supply to the input.

### Range of applications

General lighting in areas with medium humidity in hotels, restaurants, commercial spaces and residential areas.

## IT

Famiglia di incassi orientabili, protetti da polvere e umidità, equipaggiati da LED COB. Cornice da incasso in pressofusione di alluminio, verniciata a polveri con finitura sabbata.

Anello decorativo in policarbonato, verniciato in campo elettrostatico (liquido), per parti in plastica.

Elemento per montaggio di modulo LED in policarbonato nero con indicatore dell'angolo di inclinazione.

Radiatore in alluminio pressofuso, verniciato a polveri colore nero.

Riflettore in policarbonato specchiato e sfaccettato.

Diffusore in PMMA trasparente.

Guarnizione in schiuma di silicone.

Alimentatore in corrente costante fornito con ogni apparecchio, collegato direttamente ad esso da un pressacavo stagno in acciaio inossidabile.

Set di morsetti WAGO 2P (0,08-2,5 mm<sup>2</sup>) per il collegamento dell'alimentatore all'ingresso.

### Campi di applicazione

Illuminazione generale spazi con umidità media in alberghi, ristoranti, aree commerciali e residenziali.

## RO

Familie de spoturi orientabile încostrate, protejate la praf și umiditate (IP54), echipate cu un LED COB.

Rama de încostrare din aluminiu turnat, vopsită în câmp electrostatic cu finisaj sablat. Inel decorativ din policarbonat, vopsit electrostatic (lichid), pentru piese din plastic.

Elementul de montaj al modulului cu LED din policarbonat de culoare neagră, cu indicator al unghiului de înclinare.

Radiatorul modulului LED-ului din aluminiu turnat, vopsit electrostatic, culoare neagră. Reflector din policarbonat oglindat și fațetat.

Dispensur din PMMA clar.

Garnitură de etanșare din spumă siliconică.

Alimentator în curent constant livrat împreună cu corpul de iluminat, conectat direct la acesta printr-o presetupă etanșă din inox.

Set de cleme WAGO 2P (0,08-2,5 mm<sup>2</sup>) pentru conectarea alimentatorului la intrare.

### Aplicații

Illuminatul general în spații cu umiditate medie din hoteluri, restaurante, spații comerciale și zone rezidențiale.





## 6,8W/12W



# xpit

## PTD01

FINISHING AVAILABLE





Code	Finishing	Type of LED	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	Optic	CRI	Weight
PTD01WW SWH/SWH	SWH/SWH	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	660 lm	280 lm	3000K	29°	90	Ø60 mm, 0,39 kg
● PTD01NW SWH/SWH	SWH/SWH	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	705 lm	299 lm	4000K	29°	90	Ø60 mm, 0,39 kg
PTD01WW SWH/SBK	SWH/SBK	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	660 lm	280 lm	3000K	29°	90	Ø60 mm, 0,39 kg
● PTD01NW SWH/SBK	SWH/SBK	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	705 lm	299 lm	4000K	29°	90	Ø60 mm, 0,39 kg
PTD01WW SBK/SBK	SBK/SBK	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	660 lm	280 lm	3000K	29°	90	Ø60 mm, 0,39 kg
● PTD01NW SBK/SBK	SBK/SBK	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	705 lm	299 lm	4000K	29°	90	Ø60 mm, 0,39 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE

## PTD02

FINISHING AVAILABLE





Code	Finishing	Type of LED	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	Optic	CRI	Weight
PTD02WW SWH/SWH	SWH/SWH	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	660 lm	280 lm	3000K	30°	90	60x60 mm, 0,40 kg
● PTD02NW SWH/SWH	SWH/SWH	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	705 lm	299 lm	4000K	30°	90	60x60 mm, 0,40 kg
PTD02WW SWH/SBK	SWH/SBK	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	660 lm	280 lm	3000K	30°	90	60x60 mm, 0,40 kg
● PTD02NW SWH/SBK	SWH/SBK	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	705 lm	299 lm	4000K	30°	90	60x60 mm, 0,40 kg
PTD02WW SBK/SBK	SBK/SBK	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	660 lm	280 lm	3000K	30°	90	60x60 mm, 0,40 kg
● PTD02NW SBK/SBK	SBK/SBK	COB BRIDGELUX	1x6,8W	220-240V AC	300 mA / 12-21V	Included	705 lm	299 lm	4000K	30°	90	60x60 mm, 0,40 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE

**PTD03**

FINISHING AVAILABLE





Code	Finishing	Type of LED	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	Optic	CRI	Weight
PTD03WW SWH/SWH	SWH/SWH	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1040 lm	620 lm	3000K	27°	90	0,41 kg
● PTD03NW SWH/SWH	SWH/SWH	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1112 lm	663 lm	4000K	27°	90	0,41 kg
PTD03WW SWH/SBK	SWH/SBK	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1040 lm	620 lm	3000K	27°	90	0,41 kg
● PTD03NW SWH/SBK	SWH/SBK	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1112 lm	663 lm	4000K	27°	90	0,41 kg
PTD03WW SBK/SBK	SBK/SBK	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1040 lm	620 lm	3000K	27°	90	0,41 kg
● PTD03NW SBK/SBK	SBK/SBK	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1112 lm	663 lm	4000K	27°	90	0,41 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE

**PTD04**

FINISHING AVAILABLE



Code	Finishing	Type of LED	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	Optic	CRI	Weight
PTD04WW SWH/SWH	SWH/SWH	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1040 lm	600 lm	3000K	27°	90	0,42 kg
● PTD04NW SWH/SWH	SWH/SWH	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1112 lm	642 lm	4000K	27°	90	0,42 kg
PTD04WW SWH/SBK	SWH/SBK	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1040 lm	600 lm	3000K	27°	90	0,42 kg
● PTD04NW SWH/SBK	SWH/SBK	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1112 lm	642 lm	4000K	27°	90	0,42 kg
PTD04WW SBK/SBK	SBK/SBK	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1040 lm	600 lm	3000K	27°	90	0,42 kg
● PTD04NW SBK/SBK	SBK/SBK	COB BRIDGELUX	1x12W	220-240V AC	500 mA / 14-20V	Included	1112 lm	642 lm	4000K	27°	90	0,42 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE