

# xsmooth

3 YEARS  
WARRANTY



## EN

Ceiling light fittings equipped with SMD LEDs with housing of die-cast aluminum and fixing clamp of steel, electrostatically painted.

Satin acrylic diffuser.

Constant current LED driver included.

### Range of applications

General interior lighting, decorative lighting.

## RO

Plafoniere echipate cu LED-uri SMD, cu carcasa din aluminiu turnat și bridă de fixare din oțel, vopsite în câmp electrostatic.

Dispensori din acril satinat.

Alimentatoare LED în curent constant incluse.

### Aplicații

Iluminatul general de interior, iluminatul decorativ.

## IT

Plafoniere equipaggiate a LED SMD con corpo in alluminio pressofuso e staffa di fissaggio in acciaio verniciati a polveri.

Diffusore in acrilico satinato.

Alimentatori LED in corrente costante incluso.

### Campi di applicazione



Illuminazione generale d'interni, illuminazione decorativa.



**SM01**

FINISHING AVAILABLE

SWH SBK





Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
SM01WW SWH	SWH	SMD 2835 EPISTAR	10W	110-240V AC	300 mA / 24-42V DC	Included	1200 lm	797 lm	3000K	80	120°	1,00 kg
SM01WW SBK	SBK	SMD 2835 EPISTAR	10W	110-240V AC	300 mA / 24-42V DC	Included	1200 lm	797 lm	3000K	80	120°	1,00 kg
SM01NW SWH	SWH	SMD 2835 EPISTAR	10W	110-240V AC	300 mA / 24-42V DC	Included	1275 lm	847 lm	4000K	80	120°	1,00 kg
SM01NW SBK	SBK	SMD 2835 EPISTAR	10W	110-240V AC	300 mA / 24-42V DC	Included	1275 lm	847 lm	4000K	80	120°	1,00 kg

**SM02**

FINISHING AVAILABLE

SWH SBK



Code	Finishing	LED type	Power	Input voltage	Output current/voltage driver	Driver	LED flux	System flux	CCT	CRI	Optics	Weight
SM02WW SWH	SWH	SMD 2835 EPISTAR	20W	220-240V AC	600 mA / 21-35V DC	Included	2400 lm	1592 lm	3000K	80	120°	2,10 kg
SM02WW SBK	SBK	SMD 2835 EPISTAR	20W	220-240V AC	600 mA / 21-35V DC	Included	2400 lm	1592 lm	3000K	80	120°	2,10 kg
SM02NW SWH	SWH	SMD 2835 EPISTAR	20W	220-240V AC	600 mA / 21-35V DC	Included	2550 lm	1695 lm	4000K	80	120°	2,10 kg
SM02NW SBK	SBK	SMD 2835 EPISTAR	20W	220-240V AC	600 mA / 21-35V DC	Included	2550 lm	1695 lm	4000K	80	120°	2,10 kg