

**Luminaire**

 Code PLN01CCT  
 Name XPLANNER


**Measur.**

 Code PLN01CCT  
 Name XPLANNER

Luminaire Flux	1617.95 lm	Luminaire Power	18.40 W	Efficacy	87.93 lm/W	Efficiency	99.51%
Lamps Flux	1626.00 lm	Maximum value	340.21 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	280 mm 280 mm	Height Height	10 mm 10 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.061575 m2 0.002800 m2 0.002800 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.002800 m2 0.002800 m2 0.017613 m2	
Coordinate system Date Measurement Distance		CG 23-03-2020 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1626.00 lm	
Operator Temperature Humidity Notes		25.00 °C 60.00 %		Source Voltage [V] Source current [A] Photocell			

Line		Code	Luminaire Lamps		Flux [lm]	Pow. [W]	Q.ty
		PLN01CCT	Name	XPLANNER	1626.00	18.40	1
C.I.E.	46 78 96 100 100		D DIN 5040	A30			
F UTE	0.99 E		B NBN	BZ 5 / 4 / BZ 4			

Diam=280mm



C Halfplanes

180.0 — 0.0

 ULOR 0.03 %  
 DLOR 99.48 %  
 RN 0.03 %
