

**Luminaire**

 Code PLN04CCT  
 Name XPLANNER

**Measur.**

 Code PLN04CCT  
 Name XPLANNER

Luminaire Flux	2176.28 lm	Luminaire Power	24.40 W	Efficacy	89.19 lm/W	Efficiency	99.74%
Lamps Flux	2182.00 lm	Maximum value	350.40 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	330 mm 330 mm	Height Height	10 mm 10 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.085530 m2 0.003300 m2 0.003300 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.003300 m2 0.003300 m2 0.023894 m2	
Coordinate system Date Measurement Distance		CG 23-03-2020 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 2182.00 lm	
Operator Temperature Humidity Notes		25.00 °C 60.00 %		Source Voltage [V] Source current [A] Photocell			

Line		Code	Luminaire Lamps		Flux [lm]	Pow. [W]	Q.ty
		PLN04CCT	Name XPLANNER		2182.00	24.40	1
C.I.E.	47 78 96 100 100		D DIN 5040	A30			
F UTE	1.00 E		B NBN	BZ 5 / 2.5 / BZ 4			

