

Luminaire

Code SM01NW
Name XSMOOTH


Measur.

Code SM01NW
Name XSMOOTH

Luminaire Flux	846.61 lm	Luminaire Power	10.00 W	Efficacy	84.66 lm/W	Efficiency	99.95%
Lamps Flux	847.00 lm	Maximum value	394.75 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	100 mm	Width	100 mm	Height	10 mm
Rectangular Luminous Area		Length	100 mm	Width	100 mm	Height	10 mm
Horizontal Luminous Area	0.010000 m2			Emitting area on Plane 180°		0.001000 m2	
Emitting area on Plane 0°	0.001000 m2			Emitting area on Plane 270°		0.001000 m2	
Emitting area on Plane 90°	0.001000 m2			Glare area at 76°		0.003390 m2	
Coordinate system	CG			Symmetry Type		Rotosymmetrical	
Date	16-07-2020			Maximum Gamma Angle		90	
Measurement Distance	0.00			Measurement Flux		1696.00 lm	
Operator				Source Voltage [V]			
Temperature	25.00 °C			Source current [A]			
Humidity	60.00 %			Photocell			
Notes							

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
	SM01NW	Name XSMOOTH	847.00	10.00	1
C.I.E.	50 82 97 100 100	D DIN 5040	A30		
F UTE	1.00 E	B NBN	BZ 4		

100mm x 100mm



C Halfplanes

180.0 — 0.0

ULOR 0.00 %

DLOR 99.95 %

RN 0.00 %

