

Luminaire

 Code SM01WW
 Name XSMOOTH


Measur.

 Code SM01WW
 Name XSMOOTH

Luminaire Flux	796.63 lm	Luminaire Power	10.00 W	Efficacy	79.66 lm/W	Efficiency	99.95%
Lamps Flux	797.00 lm	Maximum value	394.75 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Rectangular Luminous Area	Length Length	100 mm 100 mm	Width Width	100 mm 100 mm	Height Height	10 mm 10 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.010000 m2 0.001000 m2 0.001000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.001000 m2 0.001000 m2 0.003390 m2				
Coordinate system Date Measurement Distance	CG 16-07-2020 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 90 1696.00 lm				
Operator Temperature Humidity Notes	25.00 °C 60.00 %	Source Voltage [V] Source current [A] Photocell					

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
	SM01WW	Name XSMOOTH	797.00	10.00	1
C.I.E.	50 82 97 100 100	D DIN 5040	A30		
F UTE	1.00 E	B NBN	BZ 4		

100mm x 100mm



C Halfplanes

180.0 ——— 0.0

 ULOR 0.00 %
 DLOR 99.95 %
 RN 0.00 %
