

**Luminaire**

 Code SM02WW  
 Name XSMOOTH

**Measur.**

 Code SM02WW  
 Name XSMOOTH

Luminaire Flux	1592.27 lm	Luminaire Power	20.00 W	Efficacy	79.61 lm/W	Efficiency	99.95%
Lamps Flux	1593.00 lm	Maximum value	394.75 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	200 mm	Width	100 mm	Height	10 mm
Rectangular Luminous Area		Length	200 mm	Width	100 mm	Height	10 mm
Horizontal Luminous Area	0.020000 m2	Emitting area on Plane 180°		Emitting area on Plane 270°		Emitting area on Plane 90°	0.002000 m2
Emitting area on Plane 0°	0.002000 m2	Emitting area on Plane 270°		Emitting area on Plane 90°		Emitting area on Plane 0°	0.001000 m2
Emitting area on Plane 90°	0.001000 m2	Emitting area on Plane 90°		Emitting area on Plane 0°		Emitting area on Plane 180°	0.006779 m2
Coordinate system	CG	Symmetry Type		Maximum Gamma Angle		Measurement Flux	Rotosymmetrical
Date	16-07-2020	Measurement Flux		Measurement Flux		Measurement Flux	90
Measurement Distance	0.00	Measurement Flux		Measurement Flux		Measurement Flux	1696.00 lm
Operator		Source Voltage [V]		Source current [A]		Photocell	
Temperature	25.00 °C	Source current [A]		Photocell			
Humidity	60.00 %	Photocell					
Notes							

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
	SM02WW	Name XSMOOTH	1593.00	20.00	1
C.I.E.	50 82 97 100 100	D DIN 5040	A30		
F UTE	1.00 E	B NBN	BZ 4		

